






MEDIA SECURITY SYSTEMS SRL






str. pictor Stefan Dimitrescu nr.4 bloc 19 scara C of.58, parter.Sector 4 041361 Romania

tel: (+4)021-3323508 fax: (+4)021-3326300 email:sales@mss.ro

**Oferta. Echipamente de supraveghere video****HIKVISION**



9 iulie 2010


PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
IP CCD Box Camera		
DS-2CD892PF-E 540 Linii TV* 	Camera IP, 1/3" SONY Super HAD CCD color, 540 TVL, 0.1 Lux/F:1.2, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps, Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, RTP, RTCP, ARP, ICMP, PPPoE, DHCP, FTP, UDP, DNS, DDNS, SMTP, NTP, IP,SNMP, Static, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., Dimensiuni: 63x59x114mm, Greutate: 650g	979.91
DS-2CD812PF-E 480 Linii TV* 	Camera IP, 1/3" SONY Super HAD CCD color, 480 TVL, 0.1 Lux/F:1.2, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps, Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, RTP, RTCP, ARP, ICMP, PPPoE, DHCP, FTP, UDP, DNS, DDNS, SMTP, NTP, IP,SNMP, Static, Suporta comunicatie audio in sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., Dimensiuni: 63x59x114mm, Greutate: 650g	925.41
DS-2CD802PF-E 420 Linii TV* 	Camera IP, 1/3" SONY Super HAD CCD color, 420 TVL, 0.1 Lux/F:1.2, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps, Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, RTP/RTCP, ARP, ICMP, PPPoE, DHCP, FTP, UDP, DNS, DDNS, SMTP, NTP, IP,SNMP, Static, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., Dimensiuni: 63x59x114, Greutate: 650g	838.21
IP CMOS Box Camera		
DS-2CD852F 2M Pixels* 	Camera IP, 2M Pixels, 1/3" CMOS, 1600x1200 Pixels, 0.1 Lux/F:1.2, Compresie video: MPEG-4, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 1600x1200, 1280x720, 800x600, 528x384, 704x288, 352x288, 176x144, Frame: 5fps(1600x1200), 12.5fps(1280x720), 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNPM, Suporta comunicatie audio in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/3W max., Dimensiuni: 63x59x116mm, Greutate: 650g	1088.91
*LENTILA NU ESTE INCLUSA		
DS-2CD832F-E H.264* 	Camera IP, 1/4" CMOS, 640x480 Pixels, 0.4 Lux/F:1.2, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps, Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNPM, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/3W max., Dimensiuni: 63x59x116mm, Greutate: 650g	807.69
Megapixels IP Camera		

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-2CD886BF-E 5M Pixels* 	Camera IP 5 Megapixels, 1/2.5" progressive scan CMOS CCD, 0.5 Lux/F:1.2 color, 0.1 Lux/F:1.2 B&W, Compresie video: H.264, MPEG-4, MJPEG, Compresie audio: OggVorbis, lesire video ajustabila 32Kbps ~ 16Mbps, Rezolutii suportate: 2560x1920, Frame: 8fps(2560x1920), 20fps(2048x1536), 30fps(1600x1200), FULL HD1080P, HD720P), PTZ electronic (e-PTZ), Detectie miscare, Suporta SD/SDHC, NAS, ISCSI, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNPM,HTTPS,SIP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 4/3 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: DC 12V/12W max., PoE, Dimensiuni: 68x77.4x154.5mm, Greutate: 1000g	4031.91
DS-2CD876BF 2M Pixels* 	Camera IP 2 MegaPixels, 1/1.8" SONT progressive scan CCD, 0.5 Lux/F:1.2 color, 0.05 Lux/F:1.2 B&W, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32Kbps ~ 16Mbps, Rezolutii suportate: 1600x1200, Frame: 30fps, Detectie miscare, Suporta SD/SDHC, NAS, ISCSI, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS,DDNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMPHTTPS,SIP,802.1x,IPV6, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 4/3 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: DC 12V/12W max., PoE, Dimensiuni: 68x77.4x154.5mm, Greutate: 1000g	6206.46
DS-2CD862MF-E 1.3M Pixels* 	Camera IP 1.3 MegaPixels, 1/3" SONY progressive scan CCD, 0.1 Lux/F:1.2, Compresie video: MPEG-4, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 1280x720, 640x480, Frame: 25fps, Detectie miscare, Suporta SD card pentru înregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNPM, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: AC 24V, 12VDC/4W max., PoE, Dimensiuni: 68,5x63x157,5mm, Greutate: 600g	1851.91
DS-2CD852MF-E-ICR 2M Pixels* 	Camera IP 2.0 MegaPixels, 1/3" CMOS, 1600x1200 Pixels, 0.1 Lux/F:1.2. ICR, Compresie video: MPEG-4, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 1600x1200, 1280x720, 800x600, 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), 25fps(1280x720), 12.5fps(1600x1200), Detectie miscare, Suporta SD card pentru înregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNPM, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: AC 24V, 12VDC/4W max., PoE, Dimensiuni: 64,8x63x157,5mm, Greutate: 600g	1481.31
DS-2CD852F-E 2M Pixels* 	Camera IP 2.0 MegaPixels, 1/3" CMOS, 1600x1200 Pixels, 0.1 Lux/F:1.2. Compresie video: M PEG-4, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 1600x1200, 1280x720, 800x600, 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), 25fps(1280x720), 12.5fps(1600x1200), Detectie miscare, Suporta SD card pentru înregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNPM, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: AC 24V, 12VDC/4W max., PoE, Dimensiuni: 63x59x116mm, Greutate: 600g	892.71




*LENTILA NU ESTE INCLUSA

IP IR Water-Proof Box Camera

DS-2CD892PF-IR5 540 Linii TV 	Camera IP, 1/3" SONY Super HAD CCD, 540 Linii TV, 0.Lux/F:1.2, Lentila fixa 12mm, Iluminare IR led: 50~60m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/9W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1481.31
DS-2CD892PF-IR3 540 Linii TV 	Camera IP, 1/3" SONY Super HAD CGD, 540 Linii TV, 0.Lux/F:1.2, Lentila fixa 12mm, Iluminare IR led: 30~40m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocele retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/7W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1360.32




PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-2CD892PF-IR1 540 Linii TV 	Camera IP , 1/3" SONY Super HAD CCD, 540 Linii TV, 0.Lux/F:1.2, Lentia fixa 6mm, Iluminare IR le d: 10~20m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/5.5W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1296.01
DS-2CD812P-IR5 480 Linii TV 	Camera IP, 1 /3" SONY Super HAD CCD, 480 Linii TV, 0.Lux/F:1.2, Lentia fixa 12mm, Iluminare IR led: 50~60m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/9W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1296.01
DS-2CD812P-IR3 480 Linii TV 	Camera IP, 1 /3" SONY Super HAD CCD, 480 Linii TV, 0.Lux/F:1.2, Lentia fixa 12mm, Iluminare IR led: 30~40m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/7W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1296.01
DS-2CD812P-IR1 480 Linii TV 	Camera IP , 1 /3" SONY Super HAD CCD, 480 Linii TV, 0.Lux/F:1.2, Lentia fixa 6mm, Iluminare IR le d: 10~20m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/5.5W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1165.21
DS-2CD802P-IR5 420 Linii TV 	Camera IP, 1 /3" SONY Super HAD CCD, 420 Linii TV, 0.Lux/F:1.2, Lentia fixa 12mm, Iluminare IR led: 50~60m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/9W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1230.61
DS-2CD802P-IR3 420 Linii TV 	Camera IP, 1 /3" SONY Super HAD CCD, 420 Linii TV, 0.Lux/F:1.2, Lentia fixa 12mm, Iluminare IR led: 30~40m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/7W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1165.21
DS-2CD802P-IR1 420 Linii TV 	Camera IP , 1/3" SONY Super HAD CCD, 420 Linii TV, 0.Lux/F:1.2, Lentia fixa 6mm, Iluminare IR led: 10~20m, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, IP66, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/5.5W max., Dimensiuni: 86,5x83x228mm, Greutate: 1400g	1049.67

IP Wireless Box Camera








PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-2CD892PF-W 540 Linii TV* 	Camera IP Wireles, 1/3" SONY Super HAD CCD, 540 Linii TV, 0.1 Lux/F1.2, Auto Iris, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, UDP/IP, HTTP, FTP, SMTP,NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, IEEE802.11g Wireless Criterion, Frecventa 2.4GHz, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., Dimensiuni: 63x59x114mm, Greutate: 650g	1306.91
DS-2CD812PF-W 480 Linii TV* 	Camera IP Wireles, 1/3" SONY Super HAD CCD, 480 Linii TV, 0.1 Lux/F1.2, Auto Iris, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, UDP/IP, HTTP, FTP, SMTP,NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, IEEE802.11g Wireless Criterion, Frecventa 2.4GHz, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., Dimensiuni: 63x59x114mm, Greutate: 650g	1197.91
DS-2CD802PF-W 420 LiniiTV* 	Camera IP Wireles, 1/3" SONY Super HAD CCD, 420 Linii TV, 0.1 Lux/F1.2, Auto Iris, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, UDP/IP, HTTP, FTP, SMTP,NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, IEEE802.11g Wireless Criterion, Frecventa 2.4GHz, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., Dimensiuni: 63x59x114mm, Greutate: 650g	1049.67







*LENTILA NU ESTE INCLUSA







IP CCD Mini Dome (PoE)









DS-2CD792PF-E 540 Linii TV 	Mini Dome IP, 1/3" SONY Super HAD CCD, 540 Linii TV, 0.1 Lux/F:1.2, Lentila varifocala 3.5~9mm, Iris manual, Pozitionare: 355° Pan si 90° Tilt, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, FTP, SMTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., PoE, Dimensiuni: 0145x132.8mm, Greutate: 900g	1230.61
DS-2CD712PF-E 480 Linii TV 	Mini Dome IP, 1/3" SONY Super HAD CCD, 480 Linii TV, 0.1 Lux/F:1.2, Lentila varifocala 3.5~9mm, Iris manual, Pozitionare: 355° Pan si 90° Tilt, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocoale: TCP/IP, HTTP, FTP, SMTP,NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., PoE, Dimensiuni: 0145x132.8mm, Greutate: 900g	1176.11
DS-2CD702PF-E 420 Linii TV 	Mini Dome IP, 1/3" SONY Super HAD CCD, 420 Linii TV, 0.1 Lux/F:1.2, Lentila varifocala 3.5~9mm, Iris manual, Pozitionare: 355° Pan si 90° Tilt, Compresie video: H.264, Compresie audio: OggVorbis, lesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, FTP, SMTP,NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/4W max., PoE, Dimensiuni: 0145x132.8mm, Greutate: 900g	1078.01











IP CCD Mini Dome (Support Pan-Tilt) (PoE)

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-2CD712PF-EPT 480 Linii TV 	Mini Speed Dome IP, 1/3" SONY Super HAD CCD, 480 Linii TV, 0.1 Lux/F:1.2, Lentila varifocala 3.5~9mm cu Auto Iris, PTZ: Orizontal 0~360° si Vertical 0~90°, Compresie video: H.264, Compresie audio: OggVorbis, Iesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocoale: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 RS-485 (PTZ control), Protocol: Hikvision, Pelco-D, Pelco-P, 200 Pozitii preset, 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +50°C(Indoor), Alimentare: 12VDC/12W max., PoE, Dimensiuni: 0145x159.8mm, Greutate: 2000g	Pentru moment nu se mai fabrica
IP CMOS Dome (PoE)		
DS-2CD752MF-E 2M Pixels 	Mini Dome I P, 1/3" CMOS, 1600x1200 Pixels, 0.1 Lux/F:1.2, Lentila varifocala 2.8~11mm, Iris manual, Compresie video: MPEG-4, Compresie audio: OggVorbis, Iesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 1600x1200, 1280x720, 800x600, 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), 25fps(1280x720), 12.5fps(1600x1200), Detectie miscare, Suporta SD card pentru inregistrare locala, PTZ Electronic, Protectie prin password, Protocol retea: TCP/IP, HTTP, FTP, SMTP, NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, RS-485, 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/3W max., PoE, Dimensiuni: 0145x132.8mm, Greutate: 900g	1524.91
DS-2CD732F-E H.264 	Mini Dome IP , 1/4" CMOS, 640x480 Pixels, 0.4 Lux/F:1.2, Lentila varifocala 3.5~8mm/F:1.6/M12, Iris manual, Compresie video: H.264, Compresie audio: OggVorbis, Iesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, FTP, SMTP, NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, 1 IN/OUT alarma, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/3W max., PoE, Dimensiuni: Ø145x132.8mm, Greutate: 900g	1045.31
IP CMOS Mini Dome Vandal-Proof (PoE)		
DS-2CD7153-E 2M Pixels 	IP Mini Dome Vandal-Proof, 1/3" CMOS progressive CCD, 2M Pixels, Day&Night, 0.5 Lux/F:1.2 color, 0.1 Lux/F:1.2 B&W, Lentila fixa 4mm, Compresie Video: H.264, MPEG4, MJPEG, Compresie audio: OggVorbis, Iesire video ajustabila: 32Kbps ~ 16Mbps, Rezolutie maxima: 1600x1200, Frame: 15fps(1600x1200), 25fps(1280x720), PTZ electronic(e-PTZ), Stocare: NAS, ISCSI, Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, HTTPS, SIP, 802.1x, IPV6, 1 RJ45 10M/100M ethernet, Protectie la Impact: IEC600068-2-75Eh, 50J, EN50102, mai mare de IK10, Mod de lucru: Interior, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/3W max., PoE, Dimensiuni: 100x97.5x46.5mm x 049mm(sfera lentila), Greutate: 250g	1230.61
DS-2CD7133-E 	IP Mini Dome Vandal-Proof, 1/4" CMOS CCD, Day&Night, 0.1 Lux/F:1.2 color, 0.01 Lux/F:1.2 B&W, Lentila fixa 4mm, Compresie Video: H.264, MPEG4, MJPEG, Compresie audio: OggVorbis, Iesire video ajustabila: 32Kbps ~ 8Mbps, Rezolutie maxima: 640x480, Frame: 25fps(640x480), Stocare: NAS, ISCSI, Detectie miscare, Protectie prin password, Protocol retea: TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, HTTPS, SIP, 802.1x, IPV6, 1 RJ45 10M/100M ethernet, Protectie la Impact: IEC600068-2-75Eh, 50J, EN50102, mai mare de IK10, Mod de lucru: Interior, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC/3W max., PoE, Dimensiuni: 100x97.5x46.5mm x 049mm(sfera lentila), Greutate: 250g	794.61
Vandal-Proof IP Dome (PoE)		
DS-2CD762MF-FB 1.3M Pixels 	IP Vandal- Proof Dome, 1/3" SONY progressive CCD, 1.3M Pixels (1280x960), 0.1 Lux/F:1.2, Lentila varifocala 3.3~12mm/F:1.4, Auto Iris, Compresie video: MPEG-4, Compresie audio: OggVorbis, Iesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 1280x720, 640x480, Frame: 25fps, Detectie miscare, Suporta SD card pentru inregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, FTP, SMTP, NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, RS-485, PTZ Electronic, 1 IN/OUT alarma, Protectie la Impact: IEC60068-275 test, Eh, 50J, EN50102, Mai mare de IK10, Temperatura de operare: 10°C ~ +60°C, Alimentare: 12VDC/4W max., PoE, Dimensiuni: 0156x134.5mm, Greutate: 1400g	2037.21
DS-2CD752MF-FB MPEG-4 	IP Vandal-Proof Dome, 1/3" CMOS, 1600x1200 Pixels, 0,1 Lux/F:1.2, Lentila varifocala 3.3~12mm/F:1.4, Iris Manual, Compresie video: MPEG-4, Compresie audio: OggVorbis, Iesire video ajustabila 32K ~ 2M (8Mbps max.), Rezolutii suportate: 1600x1200, 1280x720, 800x600, 704x576, 640x480, 528x384, 704x288, 352x288, 176x144, Frame: 25fps(704x576), 25fps(1280x720), 12.5fps(1600x1200), Detectie miscare, Suporta SD card pentru înregistrare locala, Protectie prin password, Protocol retea: TCP/IP, HTTP, FTP, SMTP, NTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, RS-485, PTZ Electronic, 1 IN/OUT alarma, Protectie la Impact: IEC60068-275 test, Eh, 50J, EN50102, Mai mare de IK10, Temperatura de operare: 10°C ~ +60°C, Alimentare: AC 24V, 12VDC/4W max., PoE, Dimensiuni: 0156x134.5mm, Greutate: 1400g	1666.61

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
Economic IP Pan-Tilt Dome		
 <p>DS-2CD728PF-PT*</p>	<p>IP Pan-Tilt Dome, 1/3" SONY Super HAD CCD, 752x582 Pixels, 0.1 Lux/F:1.2, Lentila fixa 3.6mm, IR 10m, Compresie video: H.264, Protocol: Hikvision, Pelco-D, Pelco-P, Detectie miscare, Protectie prin password, Suporta SD card pentru inregistrare locala, Rezolutie: 704x576, 640x480, 528x384, 704x288, 352x288, 176x144. Protocol retea: TCP/IP, HTTP, FTP, SMTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, RS-485, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC, Dimensiuni: 0125x136,5, Greutate: 450g.</p>	1339.61
 <p>DS-2CD727PF-PT*</p>	<p>IP Pan-Tilt Dome, 1/3" SONY Super HAD CCD, 500x582 Pixels, 0.1 Lux/F:1.2, Lentila fixa 3.6mm, IR 10m, Compresie video: H.264, Protocol: Hikvision, Pelco-D, Pelco-P, Detectie miscare, Suporta SD card pentru inregistrare locala, Rezolutie: 704x576, 640x480, 528x384, 704x288, 352x288, 176x144. Protocol retea: TCP/IP, HTTP, DHCP, DNS, RTP / RTCP, PPPoE (FTP, SMTP, NTP, SNMP), Suporta comunicatie in ambele sensuri, Protectie prin password, 1 RJ45 10M/100M ethernet, RS-485, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC, Dimensiuni: 125x136,5, Greutate: 450g</p>	1230.61
 <p>DS-2CD726F-PT*</p>	<p>IP Pan-Tilt Dome, 1/4" CMOS, 640x480 Pixels, 0.4 Lux/F:1.2, Lentila fixa 3.6mm, IR 10m, Compresie video: H.264, Protocol: Hikvision, Pelco-D, Pelco-P, Detectie miscare, Suporta SD card pentru inregistrare locala, Rezolutie: 704 x 576, 640 x 480, 528 x 384, 704 x 288, 352 x 288, 176 x 144 Protocol retea: HTTP, DHCP, DNS, RTP/RTCP, PPPoE, (FTP, SMTP, SNMP) Suporta comunicatie in ambele sensuri, 1 RJ45 10M/100M ethernet, RS-485, Temperatura de operare: -10°C ~ +60°C, Alimentare: 12VDC, Dimensiuni 125x136,5, Greutate: 450g.</p>	1088.91
*SURSA DE ALIMENTARE SI SUPTUL NU SANT INCLUSE		
Mid-Speed IP Dome (Outdoor & Indoor) 6" Dome		
 <p>DS-2DM1-613H</p>	<p>IP Speed Dome, 1/4" SONY ExView CCD, 480 Linii TV, 0.7 Lux Color/F:1.4, 0.01 Lux B&W/F:1.4, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Zone Private, Auto-Focus, Lentila: 4.1~73.8mm/F:1.4~F:3.0, Zoom: 18x, Zoom Digital: 12x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SMTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 1 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/30W (Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg</p>	4358.91
 <p>DS-2DM1-614H</p>	<p>IP Speed Dome, 1/4" SONY Super HAD CCD, 480 Linii TV color 520 Linii TV B&W, 0.2 Lux Color/F:1.6, 0.02 Lux B&W/F:1.6, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Auto-Focus, Lentila: 3.84~88.4mm/F:1.6~F:3.2, Zoom: 23x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SMTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 1 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/12W (50W Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg</p>	4031.91
 <p>DS-2DM1-612H</p>	<p>IP Speed Dome, 1/4" SONY Super HAD CCD, 480 Linii TV, 0.1 Lux/F:1.6, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, Auto-Focus, Lentila: 3.9~85.8mm/F:1.6~F:3.7, Zoom: 22x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SMTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 1 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/12W (50W Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg</p>	3530.51
IP High Speed Dome (Outdoor & Indoor) 6" Dome		






PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-2DF1-617H 	IP High-Speed Dome, 1/4" SONY ExView CCD, 480 Linii TV, 1.4 Lux Color/F:1.4, 0.01 Lux B&W/F:1.4, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Zone Private, Auto-Focus, Lentila: 3.4~122.4mm/F:1.6~F:4.5, Zoom: 36x, Zoom Digital: 12x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 2 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/30W(Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg	6756.91
DS-2DF1-615H 	IP High-Speed Dome, 1/4" SONY ExView CCD, 480 Linii TV, 1.0 Lux color/F:1.4, 0.01 Lux B&W/F:1.4, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Zone Private, Auto-Focus, Lentila: 3.5~91mm/F:1.4~F:3.8, Zoom: 26x, Zoom Digital: 12x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 2 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/30W(Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg	5993.91
DS-2DF1-613H 	IP High-Speed Dome, 1/4" SONY ExView CCD, 480 Linii TV, 0.7 Lux color/F:1.4, 0.01 Lux B&W/F:1.4, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Zone Private, Auto-Focus, Lentila: 4.1~73.8mm/F:1.4~F:3.0, Zoom: 18x, Zoom Digital: 12x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 2 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/30W(Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg	5557.91
DS-2DF1-611H 	IP High-Speed Dome, 1/4" SONY ExView CCD, 480 Linii TV, 1.0 Lux color/F:1.4, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Zone Private, Auto-Focus, Lentila: 4.1~73.8mm/F:1.4~F:3.0, Zoom: 18x, Zoom Digital: 12x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 2 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/30W(Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg	5339.91
NEW IP Speed Dome (Outdoor & Indoor) 6" Dome		
DS-2DF1-616H 	IP Speed Dome, 1/4" SONY Interline Transfer CCD, 540 Linii TV, 570 Linii TV B&W, 0.8 Lux Color/F:1.4, 0.04 Lux B&W/F:1.4, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Zone Private, Auto-Focus, Lentila: 3.5~105mm/F:1.4~F:3.0, Zoom: 30x, Zoom Digital: 16x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 2 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/30W(Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg	5557.91
DS-2DF1-614H 	IP Speed Dome, 1/4" SONY Super HAD CCD, 480 Linii TV color 520 Linii TV B&W, 0.2 Lux Color/F:1.6, 0.02 Lux B&W/F:1.6, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Auto-Focus, Lentila: 3.84~88.4mm/F:1.6~F:3.2, Zoom: 23x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 2 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/12W(50W Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg	4293.51







PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-2DF1-612H 	IP Speed Dome, 1/4" SONY Super HAD CCD, 480 Linii TV, 0.1 Lux/F:1.6, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, Auto-Focus, Lentila: 3.9~85.8mm/F:1.6~F:3.7, Zoom: 22x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 2 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/12W(50W Heater ON), Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, IP66, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg	3704.91
MegaPixels IP Speed Dome (Outdoor & Indoor) 6" Dome		
DS-2DF1-672 1.3M Pixels 	MegaPixels IP Speed Dome, 1/3" SONY progressive scan CCD, 1.3M Pixels, Day&Night (ICR), 0.1 Lux/F:1.6 color, 0.01 Lux/F:1.6 B&W, PAL: 1280x960, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 12.5fps(1280x960), 25fps(1280x720), 25fps(640x480), ATW, AGC, BLC, Zone Private, Auto-Focus, Lentila: 4.95~49.5mm/F:1.6, Zoom: 10x, Zoom Digital: 15x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 1 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: AC 24V/12W, Temperatura: -30°C~+60°C, Umiditate: 90% fara condensare, Dimensiune: 6 inch, 0243x287mm, Greutate: 5Kg	6647.91
IP Speed Dome (Indoor) 4" Dome		
DS-2DF1-402H 	IP Speed Dome, 1/4" SONY ExView CCD, 540 Linii TV, 1.0 Lux color/F:1.4, PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, Zone Private, Auto-Focus, Lentila: 4.2~42mm/F:1.4, Zoom: 10x, Zoom Digital: 12x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 200 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 1 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: DC 12V sau PoE/12W, Temperatura: -10°C~+50°C, Umiditate: 90% fara condensare, Dimensiune: 4 inch, 0145x132.8mm, Greutate: 2Kg	4358.91
DS-2DF1-401H 	IP Speed Dome, 1/4" SONY Interline Transfer CCD, 500 Linii TV, 570 Linii TV B&W, 0.7 Lux/F:1.4, 0.02 Lux/F:1.4(ICR ON), PAL: 704x576, Compresie video: H.264, Compresie audio: OggVorbis, Frame: 25fps(704x576), ATW, AGC, BLC, ICR, Zone Private, Auto-Focus, Lentila: 3.8~38mm/F:1.4, Zoom: 10x, Zoom Digital: 10x, Pan: 360°, Tilt: 0°~90°, Viteza Pan/Tilt: fixa sau programabila, 256 Pozitii presetabile, Protocol retea: TCP/IP, HTTP, FTP, SNTP, DHCP, DNS, SNMP, RTP, RTCP, PPPoE, 1 RJ45 10M/100M ethernet, 1 RS-485, Minim 6 USER simultan, Comunicare in ambele sensuri, Suport Mini SD Card, 3 nivele de administrare, Protectie prin ID si password, 1 IN/OUT Alarma, 1 RS-485, Protocol: Hikvision, Pelco-P, Pelco-D, Alimentare: DC 12V/12W sau PoE, Temperatura: -10°C~+50°C, Umiditate: 90% fara condensare, Dimensiune: 4 inch, 0145x132.8mm, Greutate: 2Kg	3922.91
High Performance Box Camera		
DS-2CC197P-A* 	Day & Night box camera color, 1/3" SONY Vertical Double density Interline CCD, 540 Linii TV color, 600 Linii TV B&W, ICR Filter, 0.1 Lux/F:1.2 color, 0.01 Lux B&W, Montura lentila: C/CS, Zona Privata, Auto Iris, Electronic Shutter, AGC, AWB, BLC, OSD menu, Zoom digital, 1 RS-485, Alimentare: AC 24V, DC 12V/4W(10W cu IRC ON), Temperatura: -10°C~+60°C, Dimensiune: 68x57x133.2mm, Greutate: 500g	1034.41
DS-2CC195P-A* 	Day & Night box camera color, 1/3" SONY Super HAD CCD, 540 Linii TV color, 600 Linii TV B&W, ICR Filter, 0.1 Lux/F:1.2 color, 0.002 Lux B&W, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, DNR, OSD menu, 1 RS-485, Alimentare: AC 24V, DC 12V/4W(10W cu IRC ON), Temperatura: -10°C~+60°C, Dimensiune: 68x57x133.2mm, Greutate: 500g	979.91
DS-2CC193P-A* 	Day & Night box camera color, 1/3" SONY Super HAD CCD, 540 Linii TV color, 600 Linii TV B&W, ICR Filter, 0.1 Lux/F:1.2 color, 0.01 Lux B&W, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, OSD menu, 1 RS-485, Alimentare: AC 24V, DC 12V/4W(10W cu IRC ON), Temperatura: -10°C~+60°C, Dimensiune: 68x57x133.2mm, Greutate: 500g	674.71
DS-2CC191P-A* 	Day & Night box camera color, 1/3" SONY Super HAD CCD, 540 Linii TV, 0.05 Lux/F:1.2, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, Alimentare: AC 24V, DC 12V/4W, Temperatura: -10°C~+60°C, Dimensiune: 68x57x133.2mm, Greutate: 500g	614.76







PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
 DS-2CC194P-C*	Day & Night box camera color, 1/3" SONY Super HAD CCD, 540 Linii TV color, 600 Linii TV B&W, ICR Filter, 0.1 Lux/F:1.2 color, 0.01 Lux B&W, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, OSD menu, 1 RS-485, Alimentare: AC 90V~264V/4W(10W cu IRC ON), Temperatura: -10°C~ +60°C, Dimensiune: 65x55x118mm, Greutate: 500g	598.41
 DS-2CC194P-A*	Day & Night box camera color, 1/3" SONY Super HAD CCD, 540 Linii TV color, 600 Linii TV B&W, ICR Filter, 0.1 Lux/F:1.2 color, 0.01 Lux B&W, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, OSD menu, 1 RS-485, Alimentare: DC 12V/4W(10W cu IRC ON), Temperatura: -10°C~ +60°C, Dimensiune: 65x55x118mm, Greutate: 500g	598.41
Box Camera 530 Linii TV		
 DS-2CC192P-A*	Day & Night box camera color, 1/3" SONY Super HAD CCD, 530 Linii TV, 0.1 Lux/F:1.2, Day & Night electronic, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, Alimentare: AC 24V, DC 12V/1.5W, Temperatura: -10°C~ +60°C, Dimensiune: 63x59x114mm, Greutate: 550g	402.21
 DS-2CC192P*	Day & Night box camera color, 1/3" SONY Super HAD CCD, 540 Linii TV, 0.1 Lux/F:1.2, Day & Night electronic, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, Alimentare: DC 12V/1.5W, Temperatura: -10°C~ +60°C, Dimensiune: 48x52x70mm, Greutate: 400g	369.51
480 Linii TV		
 DS-2CC112P-A*	Day & Night box camera color, 1/3" SONY Super HAD CCD, 480 Linii TV, 0.1 Lux/F:1.2, Day & Night electronic, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, Alimentare: AC 24V, DC 12V/1.5W, Temperatura: -10°C~ +60°C, Dimensiune: 63x59x114mm, Greutate: 550g	336.81
 DS-2CC112P*	Day & Night box camera color, 1/3" SONY Super HAD CCD, 480 Linii TV, 0.1 Lux/F:1.2, Day & Night electronic, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, Alimentare: DC 12V/1.5W, Temperatura: -10°C~ +60°C, Dimensiune: 48x52x70mm, Greutate: 400g	310.65
420 Linii TV		
 DS-2CC102P-A*	Day & Night box camera color, 1/3" SONY Super HAD CCD, 420 Linii TV, 0.1 Lux/F:1.2, Day & Night electronic, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, Alimentare: AC 24V, DC 12V/1.5W, Temperatura: -10°C~ +60°C, Dimensiune: 63x59x114mm, Greutate: 550g	271.41
 DS-2CC102P*	Day & Night box camera color, 1/3" SONY Super HAD CCD, 420 Linii TV, 0.1 Lux/F:1.2, Day & Night electronic, Montura lentila: C/CS, Auto Iris, Electronic Shutter, AGC, AWB, BLC, Alimentare: DC 12V/1.5W, Temperatura: -10°C~ +60°C, Dimensiune: 63x59x114mm, Greutate: 550g	260.51
480 Linii TV CMOS		
 DS-2CC132P*	Day & Night box camera color, 1/4" CMOS, 480 Linii TV, 0.1 Lux/F:1.2, Day & Night electronic, Montura lentila: C/CS, Electronic Shutter, Alimentare: DC 12V/12W, Temperatura: -10°C~ +60°C, Dimensiune: 63x59x114mm, Greutate: 550g	161.32
*LENTILA NU ESTE INCLUSA		
CONTROLLER PTZ		
 DS-1003KI	Controller PTZ, poate controla si DVR, suporta cascadare cu alta tastatura sau DVR, interfata de comunicare RS-485, Baud Rate 1200-19200bps, joystick 3D, lungime maxima 1200m,Alimetare 12V DC, Temperatura: -10°C~ +55°C,Dimensiuni: 360x 200x 108mm,Greutate 3.3 Kg	816.41







DIGITAL VIDEO RECORDER







DVR 9000 Series
9000HFI-S Series Hybrid







PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-9016HFI-S 	DVR Hybrid, 16 Ch Video IN (BNC), 2 Ch OUT Video, 8 Ch HD IP Camera, 16 Ch IN Audio, 2 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 1024x768/60Hz, 1024x768/70Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 720P, 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 6144Kbps), Redare Sincrona: 16 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M/1000M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Suporta conectare a 32 USER simultan, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	9318.41
DS-9008HFI-S 	DVR Hybrid, 8 Ch IN Video (BNC), 2 Ch OUT Video 4 Ch HD IP Camera, 8 Ch IN Audio, 2 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 1024x768/60Hz, 1024x768/70Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 720P, 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 6144Kbps), Redare Sincrona: 8 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M/1000M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Suporta conectare a 32 USER simultan, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	5884.91
9600HFI-S Series Pure NVR		
DS-9616HFI-S 	NETW O R K DVR, 16 Ch HD IP Camera, 16 Ch IN Audio, 2 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 1024x768/60Hz, 1024x768/70Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 720P, 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 6144Kbps), Redare Sincrona: 16 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M/1000M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Suporta conectare a 32 USER simultan, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	9318.41
9100HFI-S Series		
DS-9116HFI-S 	DVR, 16 Ch IN Video (BNC), 16 Ch IN Audio, 2 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 1024x768/60Hz, 1024x768/70Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 6144Kbps), Redare Sincrona: 4 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M/1000M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Suporta conectare a 32 USER simultan, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	8064.91
DS-9108HFI-S 	DVR, 8 Ch IN Video (BNC), 8 Ch IN Audio, 2 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 1024x768/60Hz, 1024x768/70Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 6144Kbps), Redare Sincrona: 4 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M/1000M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Suporta conectare a 32 USER simultan, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	5557.91








PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-9104HFI-S 	DVR , 4 C h N Video(BNC),4 Ch IN Audio, 2 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 1024x768/60Hz, 1024x768/70Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 6144Kbps), Redare Sincrona: 4 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M/1000M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Suporta conectare a 32 USER simultan, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	4249.91
DVR 8000 Series HFI-S Series		
DS-8016HFI-S 	DVR , 16 Ch IN Video (BNC),1 Ch OUT Video 16 Ch IN Audio, 1 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)	6647.91
DS-8008HFI-S 	DVR , 8 Ch IN Video (BNC),1 Ch OUT Video, 8 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)	4467.91
DS-8004HFI-S 	DVR , 4 C h IN Video(BNC),1 Ch OUT Video, 4 Ch IN Audio, 1 Ch OUT Audio, 4 IN/2 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)	3268.91
DS-8002HFI-S 	DVR , 2 C h IN Video(BNC),1 Ch OUT Video, 2 Ch IN Audio, 1 Ch OUT Audio, 4 IN/2 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)	2178.91
HTI-S Series		
DS-8016HTI-S 	DVR , 16 Ch IN Video (BNC),1 Ch OUT Video, 16 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 15fps, DCIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)	5012.91

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
 <p>DS-8012HTI-S</p>	<p>DVR, 12 Ch IN Video (BNC), 1 Ch OUT Video, 12 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 15fps, DCIF 25fps, Iesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/28W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	4685.91
 <p>DS-8008HTI-S</p>	<p>DVR, 8 Ch IN Video(BNC), 1 Ch OUT Video, 8 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4CIF 15fps, DCIF 25fps, Iesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	3595.91
 <p>DS-8004HTI-S</p>	<p>DVR, 4 Ch IN Video (BNC), 1 Ch OUT Video, 4 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4CIF 15fps, DCIF 25fps, Iesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	3050.91
HDI-S Series		
 <p>DS-8016HDI-S</p>	<p>DVR, 16 Ch Video IN (BNC), 1 Ch OUT Video, 16 Ch IN Audio, 1 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 12fps, DCIF 15fps, 2CIF 25fps, Iesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	3595.91
 <p>DS-8008HDI-S</p>	<p>DVR, 8 Ch IN Video (BNC), 1 Ch OUT Video, 8 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 12fps, DCIF 15fps, 2CIF 25fps, Iesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	2723.91
 <p>DS-8004HDI-S</p>	<p>DVR, 4 Ch IN Video(BNC), 1 Ch OUT Video, 4 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 12fps, DCIF 15fps, 2CIF 25fps, Iesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	1928.21
HCI-S Series		

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
 <p>DS-8016HCI-S</p>	<p>DVR, 16 Ch IN Video (BNC), 1 Ch OUT Video, 16 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 6fps, DCIF 8fps, 2CIF 12fps, CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 1 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	3050.91
 <p>DS-8008HCI-S</p>	<p>DVR, 8 Ch IN Video(BNC), 1 Ch OUT Video, 8 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 6fps, DCIF 8fps, 2CIF 12fps, CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 1 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	2505.91
 <p>DS-8004HCI-S</p>	<p>DVR, 4 Ch IN Video(BNC), NO Ch OUT Video, 4 Ch IN Audio, NO Ch OUT Audio, 4 IN/2 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 6fps, DCIF 8fps, 2CIF 12fps, CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), Redare Sincrona: 2 Ch, 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	1633.91
HSI-S Series		
 <p>DS-8016HSI-S</p>	<p>D V R , 16 C h IN Video (BNC), 1 Ch OUT Video, 16 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 2CIF, CIF, QCIF, Frame: 2CIF 8fps, CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	2560.41
 <p>DS-8008HSI-S</p>	<p>D V R , 8 C h IN Video (BNC), 1 Ch OUT Video, 8 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 2CIF, CIF, QCIF, Frame: 2CIF 8fps, CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), 8 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	2287.91
 <p>DS-8004HSI-S</p>	<p>DVR , 4 C h IN Video(BNC), 1 Ch OUT Video, 4 Ch IN Audio, 1 Ch OUT Audio, 4 IN/2 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, AUX.), Rezolutie VGA: 800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz, Rezolutie Inregistrare: 4 CIF, DCIF, 2CIF, CIF, QCIF, Frame: 4 CIF 8FPS, DCIF 8fps, 2CIF 15fps, CIF 25fps, lesire Video Ajustabila: 32Kbps~2048Kbps(max. 8Mbps), 4 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/70W(fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 470(D)x441(W)x90(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	1470.41
DVR 8100 Series		
HFI-S Series		







PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
 DS-8116HFI-S	NETWORK DVR, 16 Ch IN Video, 16 Ch IN Audio, 1 Ch OUT Audio, 16 Ch in Alarma, 4 Ch OUT Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/25fps, 2CIF/25fps, CIF/25fps, Redare Sincrona: 4 Ch, 8 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M/1000M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	5012.91
 DS-8108HFI-S	NETWORK DVR, 8 Ch IN Video, 8 Ch IN Audio, 1 Ch OUT Audio, 16 IN Ch Alarma, 4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/25fps, 2CIF/25fps, CIF/25fps, Redare Sincrona: 4 Ch, 8 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M/1000M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	3704.91
 DS-8104HFI-S	NETWORK DVR, 4 Ch IN Video, 4 Ch IN Audio, 1 Ch OUT Audio, 4 IN/2 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/25fps, 2CIF/25fps, CIF/25fps, Redare Sincrona: 4 Ch, 8 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M/1000M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	3159.91
HDI-S Series		
 DS-8116HDI-S	NETWORK DVR, 16 Ch IN Video, 16 Ch IN Audio, 1 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/12fps, 2CIF/25fps, CIF/25fps, Redare Sincrona: 8 Ch, 8 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M/1000M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	3704.91
 DS-8108HDI-S	NETWORK DVR, 8 Ch IN Video, 8 Ch IN Audio, 1 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/12fps, 2CIF/25fps, CIF/25fps, Redare Sincrona: 8 Ch, 8 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M/1000M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	2941.91
 DS-8104HDI-S	NETWORK DVR, 4 Ch IN Video, 4 Ch IN Audio, 1 Ch Audio OUT, 4 IN/2 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/8fps, DCIF/8fps, 2CIF/25fps, CIF/25fps, Redare Sincrona: 4 Ch, 4 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M/1000M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)	2069.91
HCI-S Series		







PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
 DS-8116HCI-S	<p>NETWORK DVR, 16 Ch IN Video, 16 Ch IN Audio, 1 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/4fps, 2CIF/12fps, CIF/25fps, Redare Sincrona: 16 Ch, 8 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)</p>	2669.41
 DS-8108HCI-S	<p>NETWORK DVR, 8 Ch IN Video, 8 Ch IN Audio, 1 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/8fps, 2CIF/16fps, CIF/25fps, Redare Sincrona: 8 Ch, 8 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)</p>	2287.91
 DS-8104HCI-S	<p>NETWORK DVR, 4 Ch IN Video, 4 Ch IN Audio, 1 Ch Audio OUT, 4 IN/2 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/8fps, DCIF/8fps, 2CIF/16fps, CIF/25fps, Redare Sincrona: 4 Ch, 4 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 3 USB2.0, Detectie Miscare, 4 Zone private pentru fiecare camera, Zoom digital, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 450(D)x450(W)x95(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)</p>	1633.91
DVR 7000 Series 7300 Series		
 DS-7316HI-S	<p>NETWORK DVR, 16 Ch IN Video, 4 Ch IN Audio, 1 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/2fps, 2CIF/12fps, CIF/25fps, Redare Sincrona: 16 Ch, 4 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 2 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 390(D)x440(W)x70(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)</p>	2178.91
 DS-7308HI-S	<p>NETWORK DVR, 8 Ch IN Video, 4 Ch IN Audio, 1 Ch Audio OUT, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/8fps, 2CIF/16fps, CIF/25fps, Redare Sincrona: 8 Ch, 4 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 2 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 390(D)x440(W)x70(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)</p>	1851.91
 DS-7304HI-S	<p>NETWORK DVR, 4 Ch IN Video, 16 Ch IN Alarma, 4 Ch OUT Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1024x768/60Hz, PAL 704x576, Rezolutie Inregistrare: 4CIF/8fps, 2CIF/16fps, CIF/25fps, Redare Sincrona: 4 Ch, 4 HDD Port SATA/2Tb, Telecomanda, Mouse, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 RS-485(keyboard control), 2 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 390(D)x440(W)x70(H)mm, 19" standard 2U pentru montare rack, Greutate: 8Kg(fara HDD si DVD)</p>	1361.41

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
7100HI Series		
 <p>DS-7108HI-S</p>	<p>N ETWOR K DVR, 8 Ch IN/out Video ,4 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), Rezolutie VGA: 1280x1024/60Hz, 1024x768/60Hz, 800x600/60Hz, PAL 704x576, Rezolutie Inregistrare: CIF/25fps, 2 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: DC 12V/30W (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate:10%~90%, Dimensiuni: 290(D)x445(W)x44(H)mm, Greutate: 3.28Kg(fara HDD si DVD)</p>	1415.91
7000HI Series		
 <p>DS-7016HI-S</p>	<p>NETWORK DVR, 16 Ch IN Video 16 Ch OUT Video, 4 Ch IN Audio, 1 Ch OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), PAL 704x576, Rezolutie Inregistrare: 2 CIF/8fps CIF/25fps, 4 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 440(W),390(D),70(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	2015.41
 <p>DS-7008HI-S</p>	<p>NETWORK DVR, 8 Ch IN/OUT Video,Nu are intrare si iesire audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), PAL 704x576, Rezolutie Inregistrare: 2CIF/8fps, CIF/25fps, 4 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 440(W),390(D),70(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	1797.41
 <p>DS-7004HI-S</p>	<p>N ETWOR K DVR, 4 Ch IN/OUT Video, 4Ch IN Audio, 1 Ch OUT Audio, 4 IN/2 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), PAL 704x576, Rezolutie Inregistrare: 4CIF/8fps, DCIF/8fps, 2CIF/15fps, CIF/25fps, 4 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet (TCP/IP, PPPoE, DHCP, DNS, DDNS, NTS, SADAP) 1 RS-232, 1 RS-485 (PTZ Control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: 100~240VAC/6.3A (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 440(W),390(D),70(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	1252.41
7200HVI Series		
 <p>DS-7216HVI-S</p>	<p>N ETW O R K DVR, 16 Ch IN/OUT Video, 4/1 Ch IN/OUT Audio, 16 IN/4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 2 lesiri Independente Video (MAIN, SPOT), VGA, PAL 704x576, Rezolutie Inregistrare: CIF/25fps, QCIF/25fps, 2 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 2 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: DC 12V/30W (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 390(D)x440(W)x70(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	1742.91
 <p>DS-7208HVI-S</p>	<p>NE TW O RK DVR, 8 Ch IN/OUT Video,4 Ch IN Audio,1 Ch OUT Audio,16 IN Ch Alarma,4 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 2 lesiri Independente Video (MAIN, SPOT), VGA, PAL 704x576, Rezolutie Inregistrare: CIF/25fps, QCIF/25fps, 2 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 2 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: DC 12V/20W (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 390(D),440(W),70(H)mm, Greutate: 8Kg(fara HDD si DVD)</p>	1306.91
 <p>DS-7204HVI-S</p>	<p>N ETWOR K DVR, 4 Ch IN Video, 1 Ch OUT Video,1 Ch IN/OUT Audio, 4 IN/1 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 3 lesiri Independente Video (VGA, MAIN, SPOT), PAL 704x576, Rezolutie Inregistrare: 4CIF/6fps, DCIF/12fps, 2CIF/12fps, CIF/25fps, 1 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: DC 12V/20W (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 315(W),230(D),45(H)mm, Greutate: 2.8Kg(fara HDD si DVD)</p>	707.41











PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-7204HVI-S/M 	NETWO RK DVR, 4 Ch IN Video, 1 Ch IN/OUT Audio, 4 IN/1 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, 2 lesiri Independente Video (MAIN, SPOT), PAL 704x576, Rezolutie Inregistrare: 4CIF/6fps, DCIF/12fps, 2CIF/15fps, CIF/25fps, 1 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: DC 12V/20W (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 230(D)x315(W)x45(H)mm, Greutate: 2.8Kg(fara HDD si DVD)	642.01
7200AHLI Series		
DS-7204AHLI-S 	NETWORK DVR, 4 Ch IN Video, 1 Ch IN/OUT Audio, 4 IN/1 OUT Ch Alarma, Compresie Video: H.264, Compresie Audio: OggVorbis, Monitor LCD 5", 3 lesiri Independente Video (VGA, MAIN, SPOT), PAL 704x576, Rezolutie Inregistrare: 4CIF/6fps, DCIF/12fps, 2CIF/12fps, CIF/25fps, 1 HDD Port SATA/2Tb, 1 RJ45 10M/100M Ethernet, 1 RS-232, 1 RS-485 (PTZ Control), 1 USB2.0, Detectie Miscare, Back-up prin USB, CD/DVD, Retea, Alimentare: DC12V/25W (fara HDD si DVD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 270(D)x20(W)x130(H)mm, Greutate: 5Kg(fara HDD si DVD)	1143.41
7600AHLI Series		
DS-7604NI-S 	NVR (Network Video Recorder), Destinat pentru IP camera, IP speed done, DVS, Recunoaste si conecteaza automat IP camera in LAN, Modifica automat IP daca apare IP conflict, Local inregistreaza 4 Ch 4CIF sau 2 Ch UXGA (1600x1200), VGA, 1 BNC Video OUT, 1 IN/OUT audio, Compresie video: H.264, Compresie audio: OggVorbis, Codare separata pe fiecare Ch (rezolutie, frame, viteza tranzmisie, calitatea imaginii, etc.), Detectie miscare, Zona privata, Zoom digital, Viteza tranzmisie variabila: 32Kbps~2Mbps(max. 8Mbps ptr. fiecare IP), 1 HDD SATA(2Tb), Alarma 4 IN/1 OUT, 2 USB2.0, 1 RJ45 10M/100M Ethernet, 1 RS-485 (PTZ Control), Telecomanda, Mouse, Alimentare: DC 12V/20W (fara HDD), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 315(D)x230(W)x44.5(H)mm, Greutate: 2.5Kg(fara HDD)	1633.91
ATM & Mobile DVR Series		
HMFI Series (Mobile DVR)		
PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-8012HMFI 	DVR Mobil, destinat special pentru supraveghere video vehicule transport valori, vehicule transport pasageri, compartimente de cale ferata, etc., 12 Ch Video IN, 2 Ch Video OUT/BNC (1Vpp, 75Ω), Compresie video: H.264, Rezolutie: 704x576, Frame: 4CIF/25fps, 12 Ch Audio IN, 2 Ch Audio OUT, Compresie Audio: OggVorbis, 2 HDD Sata/2Tb, 1 RS-232, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0 (Suporta: USB disk, USB HDD, USB DVD-RW), 1 eSATA Pentru transfer foarte rapid(Backup), 16 Ch Alarm IN, 4 Ch Alarm OUT, Oprire automata in caz de incendiu(5min.~6h), Pornire/Oprire programata, Alimentare: DC 6~36V, OUT Alimentare: DC 12.5V, Putere Consumata: 26W(fara HDD), Temperatura: -15°C~+55°C, Umiditate:10%~90%, Dimensiuni:293(D),225(W),90(H)mm, Greutate: 5Kg(fara HDD), Telecomanda speciala IR sau FIR	9808.91
DS-8008HMFI 	DVR Mobil, destinat special pentru supraveghere video vehicule transport valori, vehicule transport pasageri, compartimente de cale ferata, etc., 8 Ch Video IN, 2 Ch Video OUT/BNC (1Vpp, 75Ω), Compresie video: H.264, Rezolutie: 704x576, Frame: 4CIF/25fps, 8 Ch Audio IN, 2 Ch Audio OUT, Compresie Audio: OggVorbis, 2 HDD Sata/2Tb, 1 RS-232, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0 (Suporta: USB disk, USB HDD, USB DVD-RW), 1 eSATA Pentru transfer foarte rapid(Backup), 16 Ch Alarm IN, 4 Ch Alarm OUT, Oprire automata in caz de incendiu(5min.~6h), Pornire/Oprire programata, Alimentare: DC 6~36V, OUT Alimentare: DC 12.5V, Putere Consumata: 26W(fara HDD), Temperatura: -15°C~+55°C, Umiditate:10%~90%, Dimensiuni:293x225x90mm, Greutate: 5Kg(fara HDD), Telecomanda speciala IR sau FIR	7955.91
HMI Series (Mobile DVR)		

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-8012HMI 	DVR Mobil, destinat special pentru supraveghere video vehicule transport valori, vehicule transport pasageri, compartimente de cale ferata, etc., 12 Ch Video IN, 2 Ch Video OUT/BNC (1Vpp, 75Ω), Compresie video: H.264, Rezolutie: 704x576, Frame: CIF/25fps, 12 Ch Audio IN, 2 Ch Audio OUT, Compresie Audio: OggVorbis, 2 HDD Sata/2Tb, 1 RS-232, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0 (Suporta: USB disk, USB HDD, USB DVD-RW), 1 eSATA Pentru transfer foarte rapid(Backup), 16 Ch Alarm IN, 4 Ch Alarm OUT, Opreire automata in caz de incendiu(5min.~6h), Pornire/Opreire programata, Alimentare: DC 6~36V, OUT Alimentare: DC 12.5V, Putere Consumata: 30W(fara HDD), Temperatura: -15°C~+55°C, Umiditate:10%~90%, Dimensiuni:225(D),293(W),90(H)mm, Greutate: 5Kg(fara HDD), Telecomanda speciala IR sau FIR	5884.91
DS-8008HMI 	DVR Mobil, destinat special pentru supraveghere video vehicule transport valori, vehicule transport pasageri, compartimente de cale ferata, etc., 8 Ch Video IN, 2 Ch Video OUT/BNC (1Vpp, 75Ω), Compresie video: H.264, Rezolutie: 704x576, Frame: CIF/25fps, 8 Ch Audio IN, 2 Ch Audio OUT, Compresie Audio: OggVorbis, 2 HDD Sata/2Tb, 1 RS-232, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0 (Suporta: USB disk, USB HDD, USB DVD-RW), 1 eSATA Pentru transfer foarte rapid(Backup), 16 Ch Alarm IN, 4 Ch Alarm OUT, Opreire automata in caz de incendiu(5min.~6h), Pornire/Opreire programata, Alimentare: DC 6~36V, OUT Alimentare: DC 12.5V, Putere Consumata: 26W(fara HDD), Temperatura: -15°C~+55°C, Umiditate:10%~95%, Dimensiuni:225(D),293(W),90(H)mm, Greutate: 5Kg(fara HDD), Telecomanda speciala IR sau FIR	4576.91
PENTRU DVR-URILE DIN SERIA DS-8012HMFI, DS-8008HMFI, DS-8012HMI, DS-8008HMI, SE POATE OFERI OPTIONAL : INTERFATA VGA (800x600/60Hz, 1024x768/60Hz, 1280x1024/60Hz), INTERFATA WIRELESS NETWORK, INTERFATA GPS		
8104HMI Series (Mobile DVR)		
DS-8104HMI-A 	DVR Mobil, destinat special pentru supraveghere video vehicule transport pasageri, TAXI, tren, vehicule utilitare, etc., 4 Ch Video IN, 1 Ch Video OUT (1Vpp, 75Ω), Compresie video: H.264, Rezolutie: 704x576, Frame: 4CIF/6fps, DCIF/12fps, 2CIF/15fps, CIF/25fps, QCIF/25fps, 4 Ch Audio IN, 1 Ch Audio OUT, Compresie Audio: OggVorbis, 2 HDD Sata/2Tb, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0, 8Ch Alarm IN, 2 Ch Alarm OUT, Opreire automata in caz de incendiu(5min.~6h), Alimentare: DC 6~36V, OUT Alimentare: DC 12.5V, Putere Consumata: 6W(fara HDD), Temperatura: -15°C~+55°C, Umiditate:10%~95%, Dimensiuni:210(D),236(W),73(H)mm, Greutate: 3Kg(fara HDD), Telecomanda speciala	3268.91
DS-8104HMI-B 	DVR Mobil, destinat special pentru supraveghere video vehicule transport pasageri, TAXI, tren, vehicule utilitare, etc., 4 Ch Video IN, 2 Ch Video OUT (1Vpp, 75Ω), Compresie video: H.264, Rezolutie: 704x576, Frame: 4CIF/6fps, DCIF/12fps, 2CIF/15fps, CIF/25fps, QCIF/25fps, 1 Ch Audio IN, 1 Ch Audio OUT, Compresie Audio: OggVorbis, 2 HDD Sata/2Tb, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0, 4 Ch Alarm IN, 1 Ch Alarm OUT, Opreire automata in caz de incendiu(5min.~6h), Alimentare: DC 6~36V, OUT Alimentare: DC 12.5V, Putere Consumata: 6W(fara HDD), Temperatura: -15°C~+55°C, Umiditate:10%~95%, Dimensiuni:210(D),236(W),73(H)mm, Greutate: 3Kg(fara HDD), Telecomanda speciala	2505.91
DS-8104HMI-M 	DVR Mobil, destinat special pentru supraveghere video vehicule transport pasageri, TAXI, tren, vehicule utilitare, etc., 4 Ch Video IN, 1 Ch Video OUT (1Vpp, 75Ω), Compresie video: H.264, Rezolutie: 704x576, Frame: 4CIF/6fps, DCIF/12fps, 2CIF/15fps, CIF/25fps, QCIF/25fps, 2 Ch Audio IN, 1 Ch Audio OUT, Compresie Audio: OggVorbis, 2 HDD Sata/2Tb, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0, 2 Ch Alarm IN, 2 Ch Alarm OUT, Opreire automata in caz de incendiu(5min.~6h), Alimentare: DC 6~36V, OUT Alimentare: DC 12.5V, Putere Consumata: 5W(fara HDD), Temperatura: -10°C~+55°C, Umiditate:10%~95%, Dimensiuni:105(D)x155(W)x45(H)mm, Greutate: 1Kg(fara HDD), Telecomanda speciala	2015.41
PENTRU DVR-URILE DIN SERIA DS-8104HMI-A, DS-8104HMI-B, DS-8104HMI-M, SE POATE OFERI OPTIONAL : INTERFATA WIRELESS NETWORK, INTERFATA GPS		
8004AHI/AHLI Series (ATM/POS)		
DS-8004AHLI-S 	ATM/POS NETWORK DVR, 4 Ch Video IN, 1 OUT BNC, 1 OUT RCA, VGA: 800x600/60Hz, 1024x768/60Hz, Compresie video: H.264, Rezolutie: 704x576, Frame: CIF/25fps, QCIF/25fps, Ecran LCD 5", Vizualizare simultana: 2 Ch, 4 Ch Audio IN, 1 BNC si 1 RCA Audio OUT, Compresie Audio: OggVorbis, 1 RJ45 RS-232, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0 (Suporta: USB disk, USB HDD, USB DVD-RW), 5 Ch Alarm IN, 2 Ch Alarm OUT, 4 HDD Port SATA/2Tb, Alimentare: AC 100~240V/6.3A/70W, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 180(H)x180(W)x280(L)mm, Greutate: 5Kg	2723.91

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-8004AHI-S 	ATM/POS NETWORK DVR, 4 Ch Video IN, 1 OUT BNC, 1 OUT RCA, VGA: 800x600/60Hz, 1024x768/60Hz, Compresie video: H.264, Rezolutie: 704x576, Frame: CIF/25fps, QCIF/25fps, Vizualizare simultana: 2 Ch, 4 Ch Audio IN, 1 BNC si 1 RCA Audio OUT, Compresie Audio: OggVorbis, 1 RJ45 RS-232, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0 (Suporta: USB disk, USB HDD, USB DVD-RW), 5 Ch Alarm IN, 2 Ch Alarm OUT, 4 HDD Port SATA/2Tb, Alimentare: AC 100~240V/6.3A/70W, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 180(H)x180(W)x280(L)mm, Greutate: 5Kg	2178.91
DS-8002AHLI-S 	ATM/POS NETWORK DVR, 3 Ch Video IN, 1 OUT BNC, 1 OUT RCA, VGA: 800x600/60Hz, 1024x768/60Hz, Compresie video: H.264, Rezolutie: 704x576, Frame: CIF/25fps, QCIF/25fps, Ecran LCD 5", Vizualizare simultana: 2 Ch, 3 Ch Audio IN, 1 BNC si 1 RCA Audio OUT, Compresie Audio: OggVorbis, 1 RJ45 RS-232, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0 (Suporta: USB disk, USB HDD, USB DVD-RW), 4 Ch Alarm IN, 2 Ch Alarm OUT, 4 HDD Port SATA/2Tb, Alimentare: AC 100~240V/6.3A/70W, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 180(H)x180(W)x280(L)mm, Greutate: 5Kg	2505.91
DS-8002AHI-S 	ATM/POS NETWORK DVR, 3 Ch Video IN, 1 OUT BNC, 1 OUT RCA, VGA: 800x600/60Hz, 1024x768/60Hz, Compresie video: H.264, Rezolutie: 704x576, Frame: CIF/25fps, QCIF/25fps, Vizualizare simultana: 2 Ch, 4 Ch Audio IN, 1 BNC si 1 RCA Audio OUT, Compresie Audio: OggVorbis, 1 RJ45 RS-232, 1 RS-485, 1 RJ45 10M/100M Ethernet, 1 USB2.0 (Suporta: USB disk, USB HDD, USB DVD-RW), 4Ch Alarm IN, 2 Ch Alarm OUT, 4 HDD Port SATA/2Tb, Alimentare: AC 100~240V/6.3A/70W, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 180(H)x180(W)x280(L)mm, Greutate: 5Kg.	1993.61
Backup Device (For Mobile DVR)		
DS-1002HMI-S 	Unitate mobila de recuperare rapida (BACKUP), partial sau total a datelor stocate in DVR- urile Mobile din seria 8000, Pentru vizualizarea operatiunilor efectuate dispune de ecran LCD 5.5", Conectare cu DVR prin port eSATA (1 port) sau USB2.0 (1 port), Contine 1 port HDD SATA/2Tb, Alimentare: DC 12V/10W, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Dimensiuni: 80(D)x195(W)x170(L)mm, Greutate: 2Kg. DUPA RECUPERAREA DATELOR SE CONECTEAZA LA PC PRIN USB PORT SI SE POATE VIZUALIZA SI PROCESA DATELE TOTAL SAU NUMAI CE ESTE NECESAR.	1786.51
PC Board DVR		
4000HSI Series		
PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-4016HSI 	P C D VR , S lot PCI , 16 C h I N Vi deo , Rezolutie: 704x576, Compresie: H.264, Frame: 1~25fps, Rezolutie Compresie Timp-Real: CIF/325x288, QCIF/176x144, Rezolutie Compresie NU Timp-Real: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 16 Ch IN Audio, Compresie: OggVorbis, Transmisie Video Ajustabila (512~768Kbps optim), Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 9W, Dimensiuni: 198x100mm, SISTEM OPERARE : WINDOWS 2000, 2003, XP, Vista, Redhat 9.0, Fedora 3, Fedora 4, Fedora 5, Fedora 6, Fedora 7, Fedora 8, Cerinte minime pentru PC : CPU: SERIA INTEL, PLACA DE BAZA: CHIPSET 845, 865, 915, 925, 945, 965, Core 2, Core 4, MEMORIE: 256Mb minim, PLACA VIDEO: Nvidia Geforce MX400, 420, 440, FX5200, 5600, GeForce 6600, ATI Radeon 7000, 7500, 9000, 9200, 9550, 9600, ATI X300, X700, Intel 845G, 865G, 915G	1220.80
DS-4008HSI 	PC DVR, Slot PCI, 8 Ch IN Video, Rezolutie: 704x576, Compresie: H.264, Frame: 1~25fps, Rezolutie Compresie Timp-Real: CIF/325x288, QCIF/176x144, Rezolutie Compresie NU Timp-Real: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 8 Ch IN Audio, Compresie: OggVorbis, Transmisie Video Ajustabila (512~768Kbps optim), Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 9W, Dimensiuni: 178x99mm, SISTEM OPERARE : WINDOWS 2000, 2003, XP, Redhat 9.0, Fedora 3, Fedora 4, Fedora 5, Fedora 6, Fedora 7, Fedora 8, Cerinte minime pentru PC : CPU: SERIA INTEL, PLACA DE BAZA: CHIPSET 845, 865, 915, 925, 945, 965, Core2, Core 4, MEMORIE: 256Mb minim, PLACA VIDEO: Nvidia Geforce MX400, 420, 440, FX5200, 5600, GeForce 6600, ATI Radeon 7000, 7500, 9000, 9200, 9550, 9600, ATI X300, X700, Intel 845G, 865G, 915G	761.91
4000HCI Series		

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-4016HCI 	P C D VR, Slot PCI, 16 Ch IN Video, Rezolutie: 704x576, Compresie: H.264, Frame: 25fps, Rezolutie Compresie Timp-Real: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 16 Ch IN Audio, Compresie: OggVorbis, Transmisie Video Ajustabila / 32~1000Kbps(CIF) / 70~2000Kbps(4CIF), Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 22W, Dimensiuni: 250x106mm, SISTEM OPERARE : WINDOWS 2000, XP, Server 2003, Vista RedHat 9.0, Fedora 3, Fedora 4, Fedora 5, Cerinte minime pentru PC : CPU: SERIA INTEL, PLACA DE BAZA: CHIPSET 845, 865, 925, 945, MEMORIE: 256Mb minim, PLACA VIDEO: Nvidia Geforce MX400, 440, 4000, FX5200, 5600, GeForce 6600, ATI Radeon 7000, 7500, 8500, 9000, 9200, 9550, 9600, ATI X300, X700, X1300, X1600, Intel 845G, 865G, 915G	2178.91
DS-4008HCI-E 	P C D VR , S lot PCI Expres, 8 Ch IN Video, Rezolutie: 704x576, Compresie: H.264, Frame: 25fps, Rezolutie Compresie Timp-Real: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 8 Ch IN Audio, Compresie: OggVorbis, Transmisie Video Ajustabila / 32~1000Kbps(CIF) / 70~2000Kbps(4CIF), Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 7W, Dimensiuni: 201x109mm, SISTEM OPERARE : WINDOWS 2000, XP, Server 2003, Vista, RedHat 9.0, Fedora 3, Fedora 4, Fedora 5, Cerinte minime pentru PC : CPU: SERIA INTEL, PLACA DE BAZA: CHIPSET 845, 865, 925, 945, MEMORIE: 256Mb minim, PLACA VIDEO: Nvidia Geforce 6600, GeForce 6200, ATI X600, X550, ATI 1600, Intel 945P/PL	1388.66
DS-4008HCI 	P C DVR , S lot PCI, 8 Ch IN Video, Rezolutie: 704x576, Compresie: H.264, Frame: 25fps, Rezolutie Compresie Timp-Real: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 8 Ch IN Audio, Compresie: OggVorbis, Transmisie Video Ajustabila CIF/32~1000Kbps, 4CIF/70~2000Kbps, Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 7W, Dimensiuni: 185x107mm, SISTEM OPERARE : WINDOWS 2000, XP, Server 2003, RedHat 9.0, Vista, Fedora 3, Fedora 4, Fedora 5, Cerinte minime pentru PC : CPU: SERIA INTEL, PLACA DE BAZA: CHIPSET 845, 865, 925, 945, MEMORIE: 256Mb minim, PLACA VIDEO: Nvidia Geforce MX400, 420, 440, FX5200, 5600, GeForce 6600, ATI Radeon 7000, 7500, 9000, 9200, 9550, 9600, ATI X300, X700, Intel 845G, 865G, 915G	1388.66
DS-4004HCI 	PC DVR , S lot PCI, 4 Ch IN Video, Rezolutie: 704x576, Compresie: H.264, Frame: 25fps, Rezolutie Compresie Timp-Real: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 4 Ch IN Audio, Compresie: OggVorbis, Transmisie Video Ajustabila CIF/32~1000Kbps, 4CIF/70~2000Kbps, Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 3.5W, Dimensiuni: 155x95mm, SISTEM OPERARE : WINDOWS 2000, XP, Server 2003, RedHat 9.0, Vista, Fedora 3, Fedora 4, Fedora 5, Cerinte minime pentru PC : CPU: SERIA INTEL, PLACA DE BAZA: CHIPSET 845, 865, 925, 945, MEMORIE: 256Mb minim, PLACA VIDEO: Nvidia Geforce MX400, 420, 440, FX5200, 5600, GeForce 6600, ATI Radeon 7000, 7500, 9000, 9200, 9550, 9600, ATI X300, X700, Intel 845G, 865G, 915G	652.91
4200 Series		
DS-4216HFVI 	P C D V R , Slot PCI, 16 Ch IN Video, 16 Ch mono IN Audio, Compresie: H:264, Rezolutie: 704x576, Rezolutie Redare: 4CIF/2CIF/CIF/QCIF, Frame: 1/16~25fps, Transmisie Video Ajustabila: CIF/32~2Mbps, 4CIF/32~4Mbps, 1 OUT Video BNC (monitor/TV), 16 Ch IN Audio, Compresie: OggVorbis, Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 14W, Dimensiuni: 213x101mm, SE POT INSTALA MAXIM 4 PC DVR IN ACELASI PC (max. 64 Camere), SISTEM OPERARE : WINDOWS 2000, XP, SERVER 2003	2069.91
DS-4208HFVI 	PC DVR , S lot PCI, 8 Ch IN Video, 8 Ch mono IN Audio, Compresie: H:264, Rezolutie: 704x576, Rezolutie Redare: 4CIF/2CIF/CIF/QCIF, Frame: 1/16~25fps, Transmisie Video Ajustabila: CIF/32~2Mbps, 4CIF/32~4Mbps, 1 OUT Video BNC (monitor/TV), 8 Ch IN Audio, Compresie: OggVorbis, Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 7W, Dimensiuni: 162x101mm, SE POT INSTALA MAXIM DE PC DVR IN ACELASI PC PENTRU CATE PCI Slot EXISTA (max. 64 Camere), SISTEM OPERARE : WINDOWS 2000, XP, SERVER 2003	1415.91

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-4216HCI 	P C D V R , SI ot PCI, 16 Ch IN Video, Compresie: H:264, Rezolutie: 704x576, Rezolutie Redare: 4CIF/2CIF/CIF/QCIF, Frame: 1/16~25fps, Transmisie Video Ajustabila: CIF/32~2Mbps, 4CIF/32~4Mbps, 16 Ch IN Audio mono, Compresie: OggVorbis, Stralucire Contrast Saturatie configurabile pe fiecare Ch, Detectie de Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Putere Consumata: 14W, Dimensiuni: 213x101mm, SE POT INSTALA MAXIM 4 PC DVR IN ACELASI PC (max. 64 Camere), SISTEM OPERARE : WINDOWS 2000, XP, SERVER 2003	1415.91
4000MDI Series		
DS-4004MDI IP Matrix 	I P DECODE R & MATRIX, Slot PCI, Decodeaza 8 Ch Video&Audio CIF sau 4 Ch Video&Audio 4CIF sau 2 Ch Video&Audio 4Cif si 6 Ch Video CIF, 4 Ch Video&Audio OUT analog, SE POT MONTA IN PC PANA ACOPERA max. 64 Camere, Rezolutii: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, Putere Consumata: 7.5W, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Dimensiuni: 158x108mm, SISTEM OPERARE : WINDOWS 2000, XP, Server 2003, Vista, RedHat 9.0, Fedora 3, Fedora 4, Fedora 5, Cerinte minime pentru PC : CPU: SERIA INTEL, PLACA DE BAZA: CHIPSET 845, 865, 925, 945, MEMORIE: 256Mb minim, PLACA VIDEO: Nvidia Geforce MX400, 420, 440, FX5200, 5600, GeForce 6600, ATI Radeon 7000, 7500, 9000, 9200, 9550, 9600, ATI X300, X700, Intel 845G, 865G, 915G	1732.01
DS-4002MDI IP Matrix 	I P DECODER & MATRIX, Slot PCI, Decodeaza 4 Ch Video&Audio CIF sau 2 Ch Video&Audio 4CIF sau 1 Ch Video&Audio 4Cif si 3 Ch Video CIF, 2 Ch Video&Audio OUT analog, SE POT MONTA IN PC PANA ACOPERA max. 64 Camere, Rezolutii: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, Putere Consumata: 7.5W, Temperatura: -10°C~+50°C, Umiditate: 10%~90%, Dimensiuni: 133x96mm, SISTEM OPERARE : WINDOWS 2000, XP, Server 2003, Vista, RedHat 9.0, Fedora 3, Fedora 4, Fedora 5, Cerinte minime pentru PC : CPU: SERIA INTEL, PLACA DE BAZA: CHIPSET 845, 865, 925, 945, MEMORIE: 256Mb minim, PLACA VIDEO: Nvidia Geforce MX400, 420, 440, FX5200, 5600, GeForce 6600, ATI Radeon 7000, 7500, 9000, 9200, 9550, 9600, ATI X300, X700, Intel 845G, 865G, 915G	925.41
DVS (Digital Video Server) Embedded DVS		
DS-6104HCI-SATA 	NETWORK DIGITAL VIDEO SERVER, 4 Ch Video IN, Compresie: H.264, Rezolutie: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, Frame: 1/16~25fps, lesire Video Ajustabila: 32Kbps~2Mbps, 4 Ch Audio IN, 1 Audio OUT, Compresie : OggVorbis, 4 Alarm IN, 2 Alarm OUT, 1 RJ45 RS-232, 1 RJ45 RS-485, 1 RJ45 10M/100M Ethernet (TCP, UTP, RTP, Multicast, PPPoE, HTTP, etc.), 1 Port SATA/2Tb, Detectie Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Alimentare: AC 100~240V/6.3A/12W, Dimensiuni: 350x222x78mm, Greutate: 5Kg	925.41
DS-6101HCI-SATA 	NETWORK DIGITAL VIDEO SERVER, 1 Ch Video IN, Compresie: H.264, Rezolutie: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, Frame: 1/16~25fps, lesire Video Ajustabila: 32Kbps~2Mbps, 1 Ch Audio IN, 1 Audio OUT, Compresie : OggVorbis, 4 Alarm IN, 2 Alarm OUT, 1 RJ45 RS-232, 1 RJ45 RS-485, 1 RJ45 10M/100M Ethernet (TCP, UTP, RTP, Multicast, PPPoE, HTTP, etc.), 1 Port SATA/2Tb, Detectie Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Alimentare: AC 100~240V/6.3A/12W, Dimensiuni: 350x222x78mm, Greutate: 5Kg	805.51
DS-6104HCI 	NETWORK DIGITAL VIDEO SERVER, 4 Ch Video IN, Compresie: H.264, Rezolutie: CIF/352x288, QCIF/176x144, Frame: 1/16~25fps, lesire Video Ajustabila: 32Kbps~2Mbps, 4 Ch Audio IN, 1 Audio OUT, Compresie : OggVorbis, 4 Alarm IN, 2 Alarm OUT, 1 RJ45 RS-232, 1 RJ45 RS-485 (PTZ control), 1 RJ45 10M/100M Ethernet (TCP, UTP, RTP, Multicast, PPPoE, HTTP, etc.), Detectie Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Alimentare: DC 5V/5W, Dimensiuni: 198x123x39mm, Greutate: 1Kg	805.51
DS-6101HFI-IP 	IP NETWORK DIGITAL VIDEO SERVER, 1 Ch Video IN, Compresie: H.264, Rezolutie: 4CIF/704x576, DCIF/527x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, Frame: 25fps, lesire Video Ajustabila: 32Kbps~2Mbps, 1 Ch Audio IN, 1 Audio OUT, Compresie : OggVorbis, 1 Alarm IN/OUT, 1 RJ45 RS-232, 1 RJ45 RS-485 (PTZ control), 1 RJ45 10M/100M Ethernet (TCP, UTP, RTP, Multicast, PPPoE, HTTP, etc.), Detectie Miscare, OSD, LOGO, MASK, Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Alimentare: DC 12V/3W, Dimensiuni: 70x120x45mm, Greutate: 5 Kg	598.41
Decoder Server		
DS-6008DI 	DECODER VIDEO SERVER, 8 Ch Live, Compresie DECODING: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 1 RJ45 RS-232, 1 RJ45 RS-485, 1 RJ45 Alarm IN / OUT, 1 RJ45 10M/100M Ethernet (TCP, UTP, RTP, Multicast, DHCP, PPPoE, etc.), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Alimentare: DC 12V/7W, Dimensiuni: 419(L)x238(D)x76(H)mm, Greutate: 5Kg	3214.41

PRODUS	DESCRIERE PRODUS	PRET LEI FARA TVA
DS-6004DI 	DECODER VIDEO SERVER, 4 Ch Live, Compresie DECODING: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 1 RJ45 RS-232, 1 RJ45 RS-485, 1 RJ45 Alarm IN / OUT, 1 RJ45 10M/100M Ethernet (TCP, UTP, RTP, Multicast, DHCP, PPPoE, etc.), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Alimentare: DC 12V/7W, Dimensiuni: 419(L)x238(D)x76(H)mm, Greutate: 5Kg	2059.01
DS-6001FI 	ENCODER & DECODER VIDEO SERVER, 1 Ch Live, Compresie ENCODING & DECODING: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, Frame: 1/16~25fps, Iesire Video Ajustabila: 32Kbps~2Mbps, 1 RJ45 RS-232, 1 RJ45 RS-485, 1 RJ45 2 Ch Alarm IN / OUT, 1 RJ45 10M/100M Ethernet (TCP, UTP, RTP, Multicast, DHCP, PPPoE, etc.), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Alimentare: DC 12V/7W, Dimensiuni: 1996x122x42mm, Greutate: 2Kg	1470.41
DS-6001DI 	DECODER VIDEO SERVER, 1 Ch Live, Compresie DECODING: 4CIF/704x576, DCIF/528x384, 2CIF/704x288, CIF/352x288, QCIF/176x144, 1 RJ45 RS-232, 1 RJ45 RS-485, 1 RJ45 2Ch Alarm IN / OUT, 1 RJ45 10M/100M Ethernet (TCP, UTP, RTP, Multicast, DHCP, PPPoE, etc.), Temperatura: -10°C~+55°C, Umiditate: 10%~90%, Alimentare: DC 12V/7W, Dimensiuni: 235x136x43mm, Greutate: 2Kg	1285.11
Soluții de Stocare		
A10 Series		
DS-A1024R 	Suport Stocare Video si Audio pentru : DVR, DVS, IP Camera, Sistem Operare: Linux, Procesor: Dual-Core 1Gb Cache, HDD SATA: 24, Network Interface: 2x 1Gb NIC Ethernet, Protocol: iSCSI, NFS, CIFS, FTP, HTTP, AFP / 2000Mbps, Video Format: D1 (1Mbps)/150 line, CIF (512Kbps)/300 line, RAID: 0, 1, 5, 6, 10, 50, 60, JBOD, Temperatura: -10°C~+40°C, Umiditate: 5%~95%, Alimentare: AC 210~240V/47~63Hz/ 520W, Dimensiuni: 430x220x660mm, Greutate: 44Kg, Montare RACK	46870.00
DS-A1016R 	Suport Stocare Video si Audio pentru : DVR, DVS, IP Camera, Sistem Operare: Linux, Procesor: Dual-Core 1Gb Cache, HDD SATA: 16, Network Interface: 2x 1Gb NIC Ethernet, Protocol: iSCSI, NFS, CIFS, FTP, HTTP, AFP / 2000Mbps, Video Format: D1 (1Mbps)/150 line, CIF (512Kbps)/300 line, RAID: 0, 1, 5, 6, 10, 50, 60, JBOD, Temperatura: -10°C~+40°C, Umiditate: 5%~95%, Alimentare: AC 210~240V/47~63Hz/ 520W, Dimensiuni: 430x176x660mm, Greutate: 27Kg, Montare RACK	26160.00
DS-A1012R 	Suport Stocare Video si Audio pentru : DVR, DVS, IP Camera, Sistem Operare: Linux, Procesor: Dual-Core 1Gb Cache, HDD SATA: 12, Network Interface: 2x 1Gb NIC Ethernet, Protocol: iSCSI, NFS, CIFS, FTP, HTTP, AFP / 2000Mbps, Video Format: D1 (1Mbps)/150 line, CIF (512Kbps)/300 line, RAID: 0, 1, 5, 6, 10, 50, 60, JBOD, Temperatura: -10°C~+40°C, Umiditate: 5%~95%, Alimentare: AC 210~240V/47~63Hz/ 520W, Dimensiuni: 430x132x660mm, Greutate: 25Kg, Montare RACK	25070.00
A20 Series		
DS-A2024R 	Suport Stocare Video si Audio pentru : DVR, DVS, Sistem Operare: Linux, Procesor: 64 bit Dual-Core 2Gb Cache, HDD SATA: 24, Network Interface: 2x 1Gb NIC Ethernet, Protocol: iSCSI, NFS, CIFS, FTP, HTTP, AFP / 2000Mbps, Video Format: D1 (1 Mbps)/250 line, CIF (512Kbps)/500 line, RAID: 0, 1, 5, 6, 10, 50, 60, JBOD, Temperatura: -10°C~+40°C, Umiditate: 5%~95%, Alimentare: AC 210~240V/47~63Hz/ 570W, Dimensiuni: 430x220x660mm, Greutate: 44Kg, Montare RACK	58860.00
DS-A2016R 	Suport Stocare Video si Audio pentru : DVR, DVS, Sistem Operare: Linux, Procesor: 64 bit Dual-Core 2Gb Cache, HDD SATA: 24, Network Interface: 2x 1Gb NIC Ethernet, Protocol: iSCSI, NFS, CIFS, FTP, HTTP, AFP / 2000Mbps, Video Format: D1 (1 Mbps)/250 line, CIF (512Kbps)/500 line, RAID: 0, 1, 5, 6, 10, 50, 60, JBOD, Temperatura: -10°C~+40°C, Umiditate: 5%~95%, Alimentare: AC 210~240V/47~63Hz/ 460W, Dimensiuni: 430x176x660mm, Greutate: 27Kg, Montare RACK	36624.00
NAS Expansibile		
DS-AJ16R 	Suport Stocare Video si Audio pentru : DVR, DVS, IP Camera, Sistem Operare: Linux, Procesor: Dual-Core 512Mb Cache, HDD SATA: 16, Network Interface: 2x 1Gb NIC Ethernet, Protocol: iSCSI, NFS, CIFS, FTP, HTTP, AFP / 2000Mbps, Video Format: D1 (1Mbps)/128 line, CIF (512Kbps)/256 line, RAID: 0, 1, 5, Temperatura: -10°C~+40°C, Umiditate: 5%~95%, Alimentare: AC 210~240V/47~63Hz/ 410W, Dimensiuni: 430x176x660mm, Greutate: 18Kg, Montare RACK	10028.00
DS-AJ12R 	Suport Stocare Video si Audio pentru : DVR, DVS, IP Camera, Sistem Operare: Linux, Procesor: Dual-Core 512Mb Cache, HDD SATA: 12, Network Interface: 2x 1Gb NIC Ethernet, Protocol: iSCSI, NFS, CIFS, FTP, HTTP, AFP / 2000Mbps, Video Format: D1 (1Mbps)/128 line, CIF (512Kbps)/256 line, RAID: 0, 1, 5, Temperatura: -10°C~+40°C, Umiditate: 5%~95%, Alimentare: AC 210~240V/47~63Hz/ 360W, Dimensiuni: 430x176x660mm, Greutate: 18Kg, Montare RACK	9047.00